

HIGH PERFORMANCE

EXTRA THIN FASTENER

VELCRO® Brand Extruded Plastic Hook & Loop closure. Low profile. Adhesive suitable for a wide number of substrates (aluminum, stainless steel, glass, plywood, polyester, polyethylene and polypropylene). Low adhesive temperature resistance. Not compatible with PVC-vinyl. High tack.



CLOSURE INFORMATION		
	MATERIAL	Polypropylene Polyamide
	CYCLE LIFE	Medium
	PEEL	2 N/cm
	SHEAR	30 N/cm ²
	TENSION	10 N/cm ²
	ADHESIVE OPERATING TEMPERATURE	-15°C to +60°C

ADHESIVE SUBSTRATE COMPATIBILITY	
Aluminium Adonized	✓
Glass	✓
Painted Wallboard	✓
Plywood	✓
Polyester	✓
Polyethylene	✓
Polypropylene	✓
Stainless Steel	✓
Vinyl	✗
Formica (Polished Side)	✓
Cardboard	✓
Polycrylic	✓
Fabrics	✓

✓ Recommended ✓ Good ✗ Not Recommended

REFERENCE	EAN CODE	CONTENT	WIDTH	COLOUR	ADHESIVE	QUANTITY PER SHIPPING BOX	APPLICATION METHOD
VEL-PS20020	8412355200202	5 meters of Hook Tape 5 meters of Loop Tape	20mm	■	✓	5	Stick, staple, nail, screw
VEL-PS20019	8412355200196	5 meters of Hook Tape 5 meters of Loop Tape	20mm	□	✓	5	Stick, staple, nail, screw
VEL-PS20018	8412355200189	5 meters of Hook Tape 5 meters of Loop Tape	50mm	■	✓	5	Stick, staple, nail, screw
VEL-PS20017	8412355200172	5 meters of Hook Tape 5 meters of Loop Tape	50mm	□	✓	5	Stick, staple, nail, screw
VEL-PS20016	8412355200165	25 meters of Hook Tape 25 meters of Loop Tape	20mm	■	✓	7	Stick, staple, nail, screw
VEL-PS20015	8412355200158	25 meters of Hook Tape 25 meters of Loop Tape	20mm	□	✓	7	Stick, staple, nail, screw
VEL-PS20014	8412355200141	25 meters of Hook Tape 25 meters of Loop Tape	50mm	■	✓	4	Stick, staple, nail, screw
VEL-PS20013	8412355200134	25 meters of Hook Tape 25 meters of Loop Tape	50mm	□	✓	4	Stick, staple, nail, screw

ADHESIVE RECOMMENDATIONS OF USE



Ideal temperature from 18°C to 20°C
Relative humidity from 40% to 60%



Clean the surface



Remove paper and press



Adhesive reaches maximum performance after 24 hours



PROFESSIONAL SERIES



* Weight resistance of 50mm x 100mm of closure.

