-pixcl.com

Agrippants - Adhésifs - Colles - Magnétiques

Sté Pixc'l 26 rue du chemin vert 78610 Le Perray en Yvelines Tél. : 01 34 84 21 93 Mail : contact@by-pixcl.com

3M Industrial Adhesives and Tapes

3M[™] Cylinder Spray Adhesives

Efficient, Portable and Easy to Use

3M[™] Cylinder Spray Adhesives have benefits over more traditional spray methods. Minimal startup costs, reduced downtime, simple hose and applicator setup make cylinders an obvious choice.

Whether your priorities are improving speed of application, making spraying easier or reducing capital equipment maintenance and other costs, 3M Cylinder Spray Adhesives get you there.

Advantages and benefits:

- Very efficient speed of application and reduction of overspray
- Convenient, portable and easy to use delivery system
- Maintenance free and very low equipment costs

Other benefits include:

- More efficient spraying over large surface areas or multiple parts means virtually all adhesive is used and very little is wasted
- Easy to learn, use and train new employees to spray
- Portable for easy transition and setup for multiple stations or field work

Key features include:

• High coverage



- Non-flammable adhesives
- Greenguard Certified
- Range of open time (worklife)



146





Spray patterns from 1–18+" are achievable using 3M[™] Cylinder Spray Adhesives and various spray tips.

Where to Start

Product Selection

The lead products for 3M[™] Cylinder Adhesives are:

- 3M[™] Postforming 94 CA Cylinder Spray Adhesive
- 3M[™] Hi-Strength 94 ET Cylinder Spray Adhesive
- 3M[™] Holdfast 70 Cylinder Spray Adhesive

The majority of applications can be done with these three cylinder products.



3M[™] Postforming 94 CA Cylinder Spray Adhesive is a low telegraphing that dries quickly to reach postformable strength in 1–5 minutes. A 1–15 minute open time provides flexibility in assembly speed. 3M[™] Hi-Strength 94 ET Cylinder Spray Adhesive offers all the benefits of 3M[™] Postforming 94 CA Cylinder Spray Adhesive, but delivers a higher tack and increased bonding range.



For fast, easy foam board installation, above and below grade, simply spray and stick with 3M[™] HoldFast 70 Cylinder Spray Adhesive. Bonds foam to concrete, waterproofing, OSB and more without damaging the foam.

58

3M Industrial Adhesives and Tapes | 3M.com/Assemblysolutions

-pixcl.com

Agrippants - Adhésifs - Colles - Magnétiques

Sté Pixc'l 26 rue du chemin vert 78610 Le Perray en Yvelines Tél. : 01 34 84 21 93 Mail : contact@by-pixcl.com

Save Yourself the Hassle of Inefficient Spraying

Most common applications:

- High pressure laminate
- Foam/paper core steel door
- Upholstery
- Metal lamination
- Insulation bonding

Where to find these applications:

- Cabinet shops
- Elevator interiors
- Countertop shops
- Exhibit manufacturing
- Fixture/display manufacturing
- Office furniture

Product

60 CA

HEAVY DUT

70

77

90

92

94 CA

94 ET

98NF

74

74NF

78 ET

173

SPECIALTY

MULTI-PURPOSE

- Theatre/production sets
- Acoustic panel/partition

Application

General Purpose

Construction Marine, RV,

Polystyrene

Multi-Purpo

Laminating

Laminating

Laminating

Laminating

Laminating

Foam Bonding

Foam Bonding

Polystyrene

AM & FABR

Key Questions

Asking the right questions related to the application will help you arrive at an adhesive selection quickly and painlessly.

Use A.S.P.E.C.

- What is the **APPLICATION** you are currently using the adhesive for?
- What **SUBSTRATES** does the adhesive need to bond too?

Spray

Applicator

Applicator

Applicator

Applicator

Applicator H

Applicator H

Applicator

Applicator

Applicator

Applicator

Tips

9501, 6501

QSS tip

250050, 650050

9501, 6501, 250050

4001.6501

9501, 6501, 4001

9501.6501.4001

9501, 6501

9501.6501

Hose Swivel

Applicator 9501, 6501, 250050

- Are there special **PROCESS** details the adhesive needs to accommodate? Such as high temperatures or VOC regulations?
- What kinds of END USE stress or environment will the bond be subject to? (e.g., boat carpet and saltwater conditions or exterior applications).
- How do you determine the VALUE beyond simply the COST of a product? (e.g., Improved coverage, reduced flammability or speed of application).



3M[™] Cylinder Spray Adhesives do not atomize spray patterns with added airline. This means you get consistent even spray patterns, potentially saving rework and cleanup.



Consistent spray patterns and portable cylinders mean you can realize big improvements in efficiency and save time and labor costs.

> ray Pattern Width Wide Medium Narrow Very Wide Very Narrow Medium

3M™ Cylinder Spray A	dhesive Equip	ment and A	ccessories			
	Constant of the	the state of the		Spray Tip	Angle	Spr
Continue	A			9501	95°	
				6501	65°	
	-			4001	40°	
	9501	6501	4001	QSS*	-	
	A	A	1000	250050	25°	
				650050	65°	
			Section .	*For 3M™ HoldF	ast 70 Spray Ad	dhesive
THE REAL PROPERTY AND A DESCRIPTION OF A		State of the second	and the second			

Note: The technical information and data on these pages should be considered representative or typical only and should not be used for specification purposes

T-Fitting

3M Industrial Adhesives and Tapes | October 2019 Edition

Buses pour pistolets applicateurs pour bonbonnes de colles 3M - Fiche commerciale - Page 2/2

3M[™] Cylinder Spray Adhesive Quick Reference Guide

Bulk (%)

42

41

36

23

34

28

34

25

36

28

31

(%)

43

21

27

13

23

28

28

20

22

22

VOCs

(a/L)

>80

544

534

571

654

79

<80

254

563

248

570

QSS

2-60

1-60

1-30

1–15

1-20

1–15

1-60

1-60

1–15

1-60

1-60

Web

Web

Mist

Web

Web

Pebble

Pebble

Web

Web

Web

Web

Adhesives and Sealants