

INSTRUCCIONES DE TRABAJO

Versión nº: 2 Fecha de revisión: Septiembre 2011
IDT-605: Fichas técnicas de producto



TECHNICAL DATA

ULTRA-MATE® 742

Construction characteristics

Basic construction
Base material

Width

Overall thickness

Weight

Usage characteristics

Peel Strength with LOOP STD *

Shear Strength with LOOP STD*

Cycle life with LOOP STD*

Breaking Strength *

Shrinkage after washing (3 x 60°C) *

Colourfastness to washing UNE-EN ISO 105-C10

Colourfastness to dry cleaning ISO 105 sec/DO1

Washing resistance (3x60°C)

Sewing resistance

* Internal norm of VESA

Extruded
Polypropylene hook + Non woven

Nominal ± 1 mm

1.05 ± 0.15 mm

320 g/m² ± 40 g/m²

Minimum 0.6 N/cm

Minimum 10 N/cm²

50 % loss after 200 cycles

Minimum 60 N/cm

Maximum 2.5% (Longitudinal direction)

4 minimum

4 minimum

No delamination

Good

The information included in this Technical Sheet is based on reliable tests and trials. Average value as a reference only, not a nominal specification. Given the diversity of uses of our products we advise our customers to assure themselves that the product meets the requirements of their application. The responsibility for the application and use of the product remains with the customer.

Elaborado: J.C. Lima

Revisado: E. Ducet

Autorizado: J. Camarillo

Fecha: 15.01.13

ANEXO: IDT – 605-B

FTP 639 Versión 2

Velcro Europe, S.A.: Toda la documentación gestionada mediante el software "GESDOC" está sometida a un sistema de control de la documentación. Cualquier copia impresa debe ser considerada instantáneamente obsoleta a excepción de la "copia controlada". El contenido de este documento debe considerarse confidencial y de uso interno